light functions:	driving	position
function markings:	HR	A
luminous flux:	5500 lm	
traffic:	right-hand / left-hand	
reference mark:	50	-
maximum power:	80 W	3 W
rated voltage:	12÷24V DC	
permissible voltage:	10,5÷30V DC	
current at 13,2 V:	8 A	0,2 A
current at 28 V:	2,7 A	0,2 A
maximum current:	8 A	0,2 A
IP rating:	IP67, IP69K	
work temperature:	-40 ÷ 80 °C	
housing's material:	aluminium	
lens' material:	glass	
corrosion resistance:	ISO 9227, 500 h	
vibration resistance:	15,3G 24÷2000 Hz	
EMC Class CISPR 25:	III	
built-in connectors:	-	
other:	protection: - against overheating - against reverse polarisation	










Stylish and robust lamps dedicated for trucks.


LED technology used in driving and position light guarentees the highest efficiency.


The lamps comply with EMC Directive 2004/108/EC.
They do not emit electromagnetic interference as well as they are resistant to it's influence.
Correct polarity required.


Mounting: as a freestanding or on vertical body work panels.
The bracket parts are made of Inox steel.


It is possible to install needed connectors on wire (on request).














Cat. number	Homologation code	Light functions	driving	position	Luminous flux	5500 lm	2400 lm	Reference mark	50	25	IP rating	IP67	IP69K	Position light colour	clear	orange	Housing	black	white	Frame	black	chrome-plated	red	Cover color	black	metallic	Accessories	LED module 12V-24V	light cover	cable 0,5 m	stabilizer hole
LUM1B.62900	125		✓	✓		✓			✓			✓	✓		✓			✓			✓				✓			✓	✓	✓	