

light functions:	reversing light
function markings:	AR
luminous flux:	1600 lm
maximum power:	22W
rated voltage:	12÷24V DC
permissible voltage:	10,5÷30V DC
current at 13,2V:	1,2A
current at 28V:	0,6A
maximum current:	1,2A
colour temperature:	5000÷5500K
beam angle:	50° x 30°
IP rating:	IP67, IP69K
work temperature:	-40°C ÷ 80°C
housing's material:	polymer
lens' material:	plastic
corrosion resistance:	ISO 9227, 500h
vibration resistance:	15,3G 24÷2000Hz
EMC Class CISPR 25:	V
built-in connectors:	Deutsch DT, AMP SuperSeal 1,5
other:	protection: - against overheating - against reverse polarisation



Particularly recommended for trucks and vans.

The lamps comply with EMC Directive 2004/108/EC.

They do not emit electromagnetic interference as well as they are resistant to it's influence.

Correct polarity required.

Mounting: as a freestanding on body panels.

They can be installed in any position (standing, hanging, on side).

It is possible to install needed connectors for a version with cable (on request).

Useful parts while installing:

AMP SuperSeal 1,5 plug 2-pin - cat. No. A.07137

Deutsch plug DT06-2S 2-pin - cat. No. A.07135

Cat. number	Homologation code	Luminous flux	Rated power	IP rating	Type	Accessories	Connectors	Deutsch DT	AMP SuperSeal 1,5	Packaging / pc	carton box
CRK3A.60300	104	✓	22W	IP67	IP69K	LED module 12V-24V cable 0,5 m SuperSeal 2S Plug					1
CRK3A.60350	104	✓	✓	✓	✓	✓	✓	✓		1	1
CRK3A.60370	104	✓	✓	✓	✓	✓		✓		1	1
CRK3A.60372	104	✓	✓	✓	✓	✓	✓	✓		1	1