


light functions:	position		marker
function markings:	R1D	AD	SM1
traffic:	right-hand / left-hand		
maximum power:	0,6W		
rated voltage:	12÷24V DC		
permissible voltage:	10,5÷30V DC		
current at 13,2V:	0,02A		
current at 28V:	0,01A		
maximum current:	0,02A		
colour of light:	red	white	orange
IP rating:	IP67, IP69K		
work temperature:	-40°C ÷ 80°C		
housing's material:	plastic		
lens' material:	plastic		
corrosion resistance:	-		
vibration resistance:	15,3G 24÷2000Hz		
EMC Class CISPR 25:	III		
other:	protection: - against overheating - against reverse polarisation		



The lamps comply with EMC Directive 2004/108/EC.
They do not emit electromagnetic interference as well as they are resistant to it's influence.
They require a 12V÷24V DC power supply with any polarity.
May be installed as left-side or right-side, in horizontal or vertical position.
It is possible to install needed connectors on wire (on request).



Cat. number	Homologation code	Lamp type			Light functions	position	marker	Function markings			The light colour	red	white	orange	Accessories	cable 0,2 m	cable 0,5 m	quick coupler
		rear	front	side				R1D	AD	SM1								
ESP2.60400	113	✓				✓		✓			✓					✓		
ESP2.60403	113	✓				✓		✓			✓					✓		✓
ESP2.60410	119		✓			✓			✓			✓				✓		
ESP2.60413	119		✓			✓			✓			✓				✓		✓
ESP2.60420	120			✓			✓			✓			✓			✓		
ESP2.60423	120			✓		✓				✓			✓			✓		✓