

dimensions:	Ø138/128x81		
light functions:	passing	driving	position
function markings:	C/R		A
traffic:	right-hand		
reference mark:	-	10	-
source of light:	H4		T4W
maximum power:	60/55W		4W
rated voltage:	12V DC		
optics:	standard		
IP rating:	IP54		
housing's material:	metal		
lens' material:	glass		



Particularly recommended for tractors and slow-moving vehicles.
To be mounted in factory designed locations or in the front bumper recesses.

Useful parts while installing:
main bulb gasket - cat. No. A.05820
position light bulb holder - cat. No. A.05921



Dedicated application:

A - tractors:



Massey Ferguson: 5425, 5435, 5445, 5455, 5460, 5465, 5470, 5475, 5480, 6445, 6455, 6460, 6465, 6470, 6475, 6480, 6485, 6490, 6495, 6497, 6499, 7465, 7475, 7480, 7485, 7490, 7495, 7497, 7499, 8450, 8460, 8470, 8480

B - tractors:


John Deere: 1550, 1750, 1750V, 1850, 1850N, 1950, 1950N, 2250, 2250F, 2450, 2450F, 2650, 2650N, 2850, 3050, 3350, 3650, 4050, 4055, 4050E, 4250, 4350, 4450, 4650, 4850, 4255, 4455, 4555, 4755, 4955



A.05820



A.05921



Cat. number	Massey Ferguson No.	John Deere No.	Homologation code	Light functions	passing	driving	position	Accessories	bulb gasket	Side	right	left	Application	dedicated	Packaging / pc	carton box
RGC2.52870	3788220M91		095		✓	✓			✓		✓	✓	A		1	
RGC2.52875		AL56091	095		✓	✓	✓		✓		✓	✓	B		1	