



TECHNICAL DATA / FEATURES

- dimensions: 100x100x76
- luminous flux of the LED module: 3000 lm, 2500 lm, 2000 lm, 1500 lm
- luminous flux of the lamp: 2400 lm, 2000 lm, 1600 lm, 1200 lm
- maximum power: 30W, 29W, 25W, 19W
- nominal voltage: 12V-24V DC, 12V-48V DC
- permissible power supply voltage: 10.5V-30V DC, 10.5V-60V DC
- source of light: 6 x LED
- colour temperature: 5000-7000K
- light distribution angle: 66° x 22°
- IP rating: IP67, IP69K
- work temperature: -40°C - +80°C
- housing's material: aluminium/plastic
- lens' material: plastic
- built-in connectors: AMP Faston 250
- other: protection:
 - against overheating
 - against reverse polarisation
- bracket made of Inox steel



ADDITIONAL INFORMATION



Work lamps are used to illuminate working space near vehicles, tractors, slow-moving machines and any other places where indicated voltage is available.

The lamps comply with EMC Directive 2004/108/EC. They do not emit electromagnetic interference as well as they are resistant to it's influence.

Correct polarity required.

Replacement parts:
 neodymium magnet Ø89/500N (1 pc.) - cat. No. CAR4.51320

DIMENSIONS



Cat. number	Luminous flux				IP rating	IP67	IP69K	Accessories	LED module 12V-24V	LED module 12V-48V	handle	cable 0,22 m	cable 0,5 m	cable 8 m	switch	cigarette lighter plug	Mounting method	any	installed vertically up	rear	Bracket	neodymium magn.	CAR1	M8	Connectors	AMP Faston 250	Deutsch DT	AMP SuperSeal 1,5	Cap / Pin	
	3000 lm	2500 lm	2000 lm	1500 lm																										
LED9A.53795	✓				✓	✓		✓							✓	✓	✓	✓												
LED9A.53796	✓				✓	✓		✓							✓	✓	✓	✓												
LED6.49895		✓			✓	✓		✓							✓	✓	✓	✓												
LED6.49896			✓		✓	✓		✓							✓	✓	✓	✓												
LED6.49897			✓		✓	✓		✓							✓	✓	✓	✓												
LED6.49825		✓			✓	✓		✓							✓	✓	✓	✓						✓						
LED2.47595			✓		✓	✓		✓							✓	✓	✓	✓												
LED2.47596			✓		✓	✓		✓							✓	✓	✓	✓												
LED2.47597			✓		✓	✓		✓							✓	✓	✓	✓												
LED2.47525			✓		✓	✓		✓							✓	✓	✓	✓						✓						
LED1.46831				✓	✓	✓		✓							✓	✓	✓	✓												
LED1.46832				✓	✓	✓		✓							✓	✓	✓	✓												
LED1.46833				✓	✓	✓		✓							✓	✓	✓	✓												
LED1.46818				✓	✓	✓		✓							✓	✓	✓	✓												
LED1.46825				✓	✓	✓		✓							✓	✓	✓	✓						✓						
LED1.46834				✓	✓	✓		✓							✓	✓	✓	✓												
LED1.46835				✓	✓	✓		✓							✓	✓	✓	✓												